


Rotelle con perno CR16-IKO - CR16-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cr16-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁
	Shield type With covered outer ring	Shield type With cylindrical outer ring	Sealed type With covered outer ring	Sealed type With cylindrical outer ring						
11.112 ($\frac{7}{16}$)	CR 16				73	25.400 ($\frac{1}{16}$)	15.875 ($\frac{5}{16}$)	11.112 ($\frac{7}{16}$)	$\frac{5}{16}$ -20	12.700 ($\frac{1}{2}$)
Boundary dimensions mm(inch)										
B max	B ₂	B ₃	C ₁	S ₁	S ₂	r	Bearing dimension f Min. mm(inch)	Maximum tightening torque C	Basic dynamic load rating C ₀	Basic static load rating C ₀
17.3 (0.68)	25.400 ($\frac{1}{16}$)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{16}$)	4.702 ($\frac{3}{16}$)	3.175 ($\frac{1}{8}$)	1.911 ($\frac{3}{16}$)	17.859 ($\frac{9}{16}$)	17.4	8.910	10.800

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060462916
Diametro interno	11.112 mm
Diametro esterno	25.4 mm
Spessore	15.875 mm
Peso	73 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE