

## Rotelle con perno CR28-R-IKO - CR28-R-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cr28-r-iko>

**IKO**  
**CAM FOLLOWERS**  
Inch Series Cam Followers **With Cage/With Screwdriver Slot**

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>
	Shield type		Sealed type							
19.050 ( $\frac{3}{4}$ )	CR 28 R				365	44.450 ( $1\frac{1}{2}$ )	25.400 (1)	19.050 ( $\frac{3}{4}$ )	7/-18	22.225 ( $\frac{7}{8}$ )
Boundary dimensions mm(inch)										
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	E <sub>1</sub>	E <sub>2</sub>	F	Bearing dimension f Min. mm(inch)	Maximum tightening torque C	Basic dynamic load rating C <sub>0</sub>	Basic static load rating C <sub>0</sub>
25.8126	44.450 ( $1\frac{1}{2}$ )	11.112 ( $\frac{7}{8}$ )	0.794 ( $\frac{1}{8}$ )	4.762 ( $\frac{3}{8}$ )	3.969 ( $\frac{5}{16}$ )	1.588 ( $\frac{1}{8}$ )	22.543 ( $1\frac{1}{8}$ )	100	25 100	38 200

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060463029
Diametro interno	19.05 mm
Diametro esterno	44.45 mm
Spessore	25.4 mm
Peso	365 g
Imballaggio	-

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE