


## Rotelle con perno CR12-VBUUR-IKO - CR12-VBUUR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cr12-vbuur-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



CR12-VBUUR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Spigot type With groove outer ring	Spigot type With cylindrical outer ring							
9.525 ( $\frac{3}{8}$ )			CR 12	VBUUR	36	19.050 ( $\frac{3}{4}$ )	12.700 ( $\frac{1}{2}$ )	9.525 ( $\frac{3}{8}$ )	$\frac{1}{4}$ -24	9.525 ( $\frac{3}{8}$ )	
Boundary dimensions mm(inch)						Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N		
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>					H	r
14.2 (0.56)	22.225 ( $\frac{7}{8}$ )	6.350 ( $\frac{1}{4}$ )	0.794 ( $\frac{1}{16}$ )	4.762 ( $\frac{3}{16}$ )	2.381 ( $\frac{1}{8}$ )	4.762 ( $\frac{3}{16}$ )	0.794 ( $\frac{1}{16}$ )	13.484 ( $\frac{1}{2}$ )	10.8	8.710	12.300

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060463456
Diametro interno	9.525 mm
Diametro esterno	19.05 mm
Spessore	12.7 mm
Peso	36 g
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE