


## Rotelle con perno CR20-VBUUR-IKO - CR20-VBUUR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cr20-vbuur-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



CR20-VBUUR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d <sub>1</sub>	G UNF	G <sub>1</sub>	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring							
12.700 ( $\frac{1}{2}$ )			CR 20	VBUUR	137	31.750 ( $\frac{1}{2}$ )	19.050 ( $\frac{3}{4}$ )	12.700 ( $\frac{1}{2}$ )	$\frac{1}{4}$ -20	15.875 ( $\frac{5}{8}$ )	
Boundary dimensions mm (inch)						Mounting dimension f Min. mm (inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N		
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>					H	r
20.4 (0.80)	31.750 ( $\frac{1}{2}$ )	7.938 ( $\frac{5}{16}$ )	0.794 ( $\frac{1}{16}$ )	4.792 ( $\frac{3}{4}$ )	3.175 ( $\frac{1}{4}$ )	6.350 ( $\frac{1}{4}$ )	1.588 ( $\frac{1}{8}$ )	21.828 ( $\frac{7}{8}$ )	27.7	23 600	31 700

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060463760
Diametro interno	12.7 mm
Diametro esterno	31.75 mm
Spessore	19.05 mm
Peso	137 g
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE