

Rotelle con perno CR32-VBUUR-IKO - CR32-VBUUR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cr32-vbuur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Screwdriver Slot



CR32-VBUUR

Stud dia. mm (inch)	Identification number				Mass (Ref.) g	D	C	d ₁	G UNF	G ₁	
	Shield type With cover outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring	Shield type With cylindrical outer ring							
22.225 ($\frac{7}{8}$)			CR 32	VBUUR	627	50.800 (2)	31.750 (1) ($\frac{5}{8}$)	22.225 ($\frac{7}{8}$)	$\frac{1}{4}$ -14	25.400 (1)	
Boundary dimensions mm (inch)						Mounting dimension f Min. mm (inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N		
B max	B ₂	B ₃	C ₁	g ₁	g ₂					H	r
33.5 (1.32)	50.800 (2)	12.700 ($\frac{1}{2}$)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	4.762 ($\frac{3}{16}$)	11.112 ($\frac{7}{16}$)	1.588 ($\frac{1}{16}$)	37.305 (1) ($\frac{3}{4}$)	162	45 700	80 600

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060464231
Diametro interno	22.225 mm
Diametro esterno	50.8 mm
Spessore	31.75 mm
Peso	627 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE