

## Rotelle con perno CR36-V-IKO - CR36-V-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/cr36-v-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inchi)	Identification number				Mass (Ref.)					
	Shield type With cover With cylindrical outer ring		Sealed type With shield With cylindrical outer ring		$\phi$	D	C	$d_1$	G UNF	G <sub>1</sub>
22.225 ( $\frac{7}{8}$ )		CR 36 V			759	57.150 (2 $\frac{1}{4}$ )	31.750 (1 $\frac{1}{4}$ )	22.225 (7/8)	$\frac{1}{2}$ -14	25.400 (1)
Boundary dimensions mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N		
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	$\phi$ <sub>1</sub>					$\phi$ <sub>2</sub>	r
33.5 (1.32)	33.800 (1)	12.700 ( $\frac{1}{2}$ )	8.794 ( $\frac{5}{8}$ )	4.762 ( $\frac{3}{8}$ )	4.762 ( $\frac{3}{8}$ )	1.588 ( $\frac{1}{8}$ )	31.268 (1 $\frac{1}{8}$ )	162	45 700	80 800

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060464262
Diametro interno	22.225 mm
Diametro esterno	57.15 mm
Spessore	31.75 mm
Peso	759 g
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE