

Rotelle con perno CRH24-VUUR-IKO - CRH24-VUUR-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/rotelle-perno/crh24-vuur-iko>

IKO

CAM FOLLOWERS

Inch Series Heavy Duty Cam Followers Full Complement Type/With Screwdriver Slot



| Stud dia. mm (inch) | Identification number | | Mass (Ref.) g | CRH-VUUR | | | | | | |
|------------------------------|-----------------------|----------------|---------------------|--|--|--|--|----------------|--------------|-------------|
| | Shield type | Sealed type | | D | C | d ₁ | G UNF | G ₁ | B max | |
| 22.225 (.875) | CRH 24 | VUUR | 296 | 38.100 (.875) | 22.225 (.875) | 22.225 (.875) | 1/4 | 14 | 19.050 (.75) | 24.3 (0.96) |
| Boundary dimensions mm(inch) | | | | Mounting dimension f Min. mm(inch) | Maximum tightening torque N-m | Basic dynamic load rating C N | Basic static load rating C ₀ N | | | |
| B ₂ | B ₃ | C ₁ | S ₁ | | | | | S ₂ | R | |
| 38.100 (.875) | 9.525 (.375) | 1.588 (.0625) | 4.762 (.1875) | 2.381 (.095) | 500.30 | 26.988 (1.0625) | 162 | 29 200 | 40 100 | |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952463469 |
| Diametro interno | 22.225 mm |
| Diametro esterno | 38.1 mm |
| Spessore | 22.225 mm |
| Peso | 296 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE