


Ralle regispinta GS60130-IKO - GS60130-IKO

<https://www.123cuscinetti.ch/accessori/rondella/ralle-regispinta/g60130-iko>

IKO
THRUST BEARINGS
Thrust Roller Bearings



| Shaft dia. mm | Identification number | | | | | | | |
|---------------|-----------------------|---------------|-----------------------|---------------|------------|------------|---------------|--|
| | Thrust roller bearing | Mass (Ref.) g | Thrust roller bearing | Mass (Ref.) g | Inner ring | Outer ring | Mass (Ref.) g | |
| 60 | AZ 6013026 | 2 090 | AZK 6013010 | 790 | WS 60130 | GS 60130 | 660 | |

| Boundary dimensions mm | | | | | | | | | | Standard mounting dimensions mm | | Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽²⁾ |
|------------------------|-----|----|----------------|----------------|----------------|---|--------------------|----------------|----------------|---------------------------------|---------------------|-----------------------------|---|---|
| d | D | T | d _c | D _c | D _w | B | r _s (1) | C ₁ | C ₂ | d _s Min. | D _s Max. | N | N | rpm |
| 60 | 130 | 26 | 60.05 | 129.5 | 10 | 8 | 1.5 | 79 | 119 | 119 | 80 | 158 000 | 634 000 | 3 000 |

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3616060466860 |
| Diametro interno | 60 mm |
| Diametro esterno | 130 mm |
| Spessore | 8 mm |
| Materiale | ACCIAIO |
| Peso | 650 g |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE