


Ralle regispinta GS170230-IKO - GS170230-IKO

<https://www.123cuscinetti.ch/accessori/rondella/ralle-regispinta/gs170230-iko>

IKO
THRUST BEARINGS
Thrust Roller Bearings



Shaft dia. mm	Identification number						
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
170	AZ 17023045	6 220	AZK 17023019	2 420	WS 170230	GS 170230	1 900

Boundary dimensions mm										Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d _s Min.	D _s Max.	N	N	rpm
170	230	45	170.1	229	19	13	1.5	183	221	220	184	406 000	1 730 000	1 500

Notes: (*) Minimum allowable value of chamfer dimension r
(1) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060467263
Diametro interno	170 mm
Diametro esterno	230 mm
Spessore	13 mm
Materiale	ACCIAIO
Peso	1900 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE