



Ralle regispinta GS220290-IKO - GS220290-IKO

<https://www.123cuscinetti.ch/accessori/rondella/ralle-regispinta/gs220290-iko>

 **THRUST BEARINGS**

Thrust Roller Bearings



Shaft dia. mm	Identification number						
	Thrust roller bearing	Mass (Ref.) g	Thrust roller bearing	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
220	AZ 22029050	10 400	AZK 22029022	4 290	WS 220290	GS 220290	3 060

Boundary dimensions mm										Standard mounting dimensions mm	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	
d	D	T	d _c	D _c	D _w	B	r _s (1)	C ₁	C ₂	d _s Min.	D _s Max.	N	N	rpm
220	290	50	220.15	289	22	14	2	236	290	278	237	557 000	2 530 000	1 300

Notes: ^(*) Minimum allowable value of chamfer dimension r
⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3616060467423
Diametro interno	220 mm
Diametro esterno	290 mm
Spessore	14 mm
Materiale	ACCIAIO
Peso	3060 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE