

Teste a snodo SI
DSIL5-T-K-DURBAL - DSIL5-T-K-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/dsil5-t-k-durbal>

DSIL5-T-K

female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


Red end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
maintenance free



order number		measurement [mm]							
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4	
DSIL 5 T/K		5	M 5	8	6,00	18	8,5	11	

type	measurement [mm]			load rating C0 [N]	weight [g]
	l1 min	W	h		
DSI / DSIL 5 T/K	10	9	27	6,0	0,016

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952489070
Diametro interno	5 mm
Diametro esterno	18 mm
Spessore	8 mm
Tipo	SI
Peso	16 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE