

Teste a snodo SI DSIL5-T-K-DURBAL - SIL5-T-K-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/sil5-t-k-durbal>

DSIL5-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
DSIL	S T/K	5	M 5	8	6,00	18	8,5	11

type	measurement [mm]			h	d ₁ PT	load rating C ₀ [N]	weight [kg]
	l ₁ min	W					
DSI / DSIL	S T/K	10	9	27	13	6,0	0,016

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952489070
Diametro interno	5 mm
Diametro esterno	18 mm
Spessore	8 mm
Tipo	SI
Peso	16 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE