

## Teste a snodo SI SI30M27X2-T-K-DURBAL - SI30M27X2-T-K-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/si30m27x2-t-k-durbal>


### SI30M27X2-T-K



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



rod end body:  
surface zinc plated

sliding combination:  
steel / bronze-PTFE composite

inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

outer ring:  
brass body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
SI 30 TIK M 27 x 2		30	M 27 x 2	37	25,00	70	40,0	50

type	measurement [mm]			load rating C <sub>10</sub> [N]	weight [kg]
	l <sub>3</sub> min	W	h		
SI / SIL 30 TIK M 27 x 2	51	41	110	17	114,0

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952489766
Diametro interno	30 mm
Diametro esterno	70 mm
Spessore	37 mm
Tipo	SI
Peso	1100 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE