

Teste a snodo SI SIL40-T-K-DURBAL - SIL40-T-K-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/sil40-t-k-durbal>


SIL40-T-K



female thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.



rod end body:
surface zinc plated

sliding combination:
steel / bronze-PTFE composite

inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

outer ring:
brass body pressed around, outer race
lined with bronze-PTFE composite

lubrication:
maintenance free

order number	right hand thread		measurement [mm]						
	left hand thread		d	G	B	C ₁	d ₂	d ₃	d ₄
SIL 40 T/K			40	M 42 x 2	49	33,00	91	53,0	65

type	measurement [mm]			h	d ₁ PT	load rating C ₅ [kN]	weight [kg]
	l ₁ min	W					
SI / SIL 40 T/K	60	55	142	17			2,400

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952489810
Diametro interno	40 mm
Diametro interno	1.575" inch
Diametro esterno	91 mm
Diametro esterno	3.583" inch
Spessore	49 mm
Spessore	1.929" inch
Tipo	SI
Peso	2400 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE