

## Teste a snodo SA SAL20-T-K-DURBAL - SAL20-T-K-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/sal20-t-k-durbal>

### SAL20-T-K



**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

**male thread:** maintenance free, according to DIN ISO 12240-4, series K


**Rod end body:** surface zinc plated

**Sliding combination:** steel / bronze-PTFE composite

**Inner ring:** bearing steel, hardened, ground and spherical surface chromium plated

**Outer ring:** brass body pressed around, outer race lined with bronze-PTFE composite

**Lubrication:** maintenance free



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SAL 20 T/K		20	M 20 x 1,5	25	18,00	50

type	measurement [mm]		h	α [°]	Tragzahlen C <sub>10</sub> [kN]	weight [kg]
	l <sub>1</sub> min	l <sub>2</sub>				
SA / SAL 20 T/K	45	25	78	14	57,0	0,380

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952490243
Diametro interno	20 mm
Diametro esterno	50 mm
Spessore	25 mm
Tipo	-
Peso	380 g
Il filo	-
Lubrificazione	-
Imballaggio	-
Standard	-

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE