

Teste a snodo SA SAL28-T-K-DURBAL - SAL28-T-K-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/sal28-t-k-durbal>

SAL28-T-K



Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.

male thread: maintenance free, according to DIN ISO 12240-4, series K


Rod end body: surface zinc plated

Sliding combination: steel / bronze-PTFE composite

Inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: brass body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
SAL 28 T/K		28	M 27 x 2	35	24,00	66

type	measurement [mm]		h	α [°]	Tragzahlen C ₁₀ [kN]	weight [kg]
	l ₁ min	l ₂				
SA / SAL 28 T/K	62	33	103	15	107,0	0,800

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952490335
Diametro interno	28 mm
Diametro esterno	66 mm
Spessore	35 mm
Tipo	SA
Peso	800 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE