

## Teste a snodo SI DSSI5-T-K-DURBAL - DSSI5-T-K-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/dssi5-t-k-durbal>

### DSSI5-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

**Description:** DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number	right hand thread	left hand thread	measurement [mm]						
DSSI 5 T/K	5	M 5	8	B	C1	d1	d2	d3	d4

type	measurement [mm]				load rating C <sub>0</sub> [kN]	weight [g]
	l <sub>1</sub> min	W	h	α [°]		
DSSI / DSSIL 5 T/K	10	9	27	13	6,0	0,016

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952491059
Diametro interno	5 mm
Diametro esterno	18 mm
Spessore	8 mm
Tipo	SI
Peso	16 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE