

Teste a snodo SI DSSIL8-T-K-DURBAL - DSSIL8-T-K-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/dssil8-t-k-durbal>

DSSIL8-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number	right hand thread	left hand thread	measurement [mm]							
DSSIL 8 T/K			d	G	B	C1	d1	d2	d3	d4
			8	M 8	12	9,00	24	12,5	16	

type	measurement [mm]			α °FS	load rating C ₀ [kN]	weight [kg]
	l ₁ min	W	h			
DSSIL / DSSIL 8 T/K	16	14	36	14	12,5	0,047

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952491165
Diametro interno	8 mm
Diametro esterno	24 mm
Spessore	12 mm
Tipo	SI
Peso	47 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE