

Teste a snodo SI SSIL30-T-K-DURBAL - SSIL30-T-K-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/ssil30-t-k-durbal>

SSIL30-T-K



female thread: maintenance free, according to DIN ISO 12240-4, series K, in stainless steel

Description: DIN ISO rod end K series. Made of spherical plain bearing DG...PW pressed into rod end body. Sliding combination steel / bronze-PTFE composite.


Red end body: stainless steel

Sliding combination: steel / bronze-PTFE composite

Inner ring: stainless steel, hardened and ground

Outer ring: stainless steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number	right hand thread	left hand thread	measurement [mm]							
SSIL 30 T/K			d	G	B	C ₁	d ₁	d ₂	d ₃	d ₄
			30	M 30 x 2	37	25,00	70	40,0	50	

type	measurement [mm]				α °FS	load rating C ₀ [kN]	weight [kg]
	l ₁ min	W	h				
SSI / SSIL 30 T/K	S1	41	110	17	114,0	1,100	

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952491721
Diametro interno	30 mm
Diametro esterno	70 mm
Spessore	37 mm
Tipo	SI
Peso	1100 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE