

## Teste a snodo SI DSIL5-PK-DURBAL - DSIL5-PK-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/dsil5-pk-durbal>

### DSIL5-PK



female thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.


rod end body: carbon case plated

Sliding combination: steel / bronze-PTFE composite

inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number	d	G	measurement (mm)				
right hand thread	S	M 5	8	6,00	19	9,0	11
<b>DSIL 5 PK</b>							

type	l <sub>1</sub> min	measurement (mm)			lead rating	weight
		W	h	α [°]	C <sub>0</sub> (DN)	(kg)
DSI / DSIL 5 PK	10	9	27	12	6,00	0,018

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952491806
Diametro interno	5 mm
Diametro esterno	19 mm
Spessore	8 mm
Tipo	SI
Peso	18 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE