

## Teste a snodo SI DSIL8-PK-DURBAL - DSIL8-PK-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/dsil8-pk-durbal>

### DSIL8-PK



female thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.


rod end body: surface case plated

Sliding combination: steel / bronze-PTFE composite

inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number	measurement (mm)					
right hand thread	d	G	B	C	d <sub>2</sub>	d <sub>4</sub>
DSIL 8 PK	8	M 8	12	9,00	25	12,5

type	measurement (mm)				load rating C <sub>0</sub> (kN)	weight (kg)
	l <sub>1</sub> min	w	h	α [°]		
DSI / DSIL 8 PK	16	14	36	12	12,90	0,047

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952491875
Diametro interno	8 mm
Diametro esterno	25 mm
Spessore	12 mm
Tipo	SI
Peso	47 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE