

Teste a snodo SI DSIL10-PK-DURBAL - DSIL10-PK-DURBAL


<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/dsil10-pk-durbal>

DSIL10-PK



female thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



rod end body:
surface case plated

Sliding combination:
steel / bronze-PTFE composite

inner ring:
bearing steel hardened and ground

Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	d	G	measurement (mm)				
right hand thread	10	M 10	14	11,00	29	15,0	19
DSIL 10 PK							

type	measurement (mm)			alpha	load rating	weight
	l ₁ min	W	h	[°]	C ₀ [kN]	[kg]
DSI / DSIL 10 PK	20	17	43	12	18,00	0,077

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952491899
Diametro interno	10 mm
Diametro esterno	29 mm
Spessore	14 mm
Tipo	SI
Peso	77 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE