

## Teste a snodo SI DSIL22-PK-DURBAL - DSIL22-PK-DURBAL


<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/dsil22-pk-durbal>

### DSIL22-PK



female thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



rod end body:  
surface case plated

Sliding combination:  
steel / bronze-PTFE composite

inner ring:  
bearing steel hardened and ground

Outer ring:  
rod end body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
maintenance free

order number	d	G	measurement (mm)	B	C1	d1	d2	d3	d4
right hand thread	22	M 22 x 1,5	28	20,00	55	30,0	38		
<b>DSIL 22 PK</b>									

type	l <sub>1</sub> min	W	h	alpha [°]	load rating C <sub>0</sub> (N)	weight (kg)
<b>DSI / DSIL 22 PK</b>	37	32	84	15	68,00	0,540

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952492261
Diametro interno	22 mm
Diametro esterno	55 mm
Spessore	28 mm
Tipo	SI
Peso	540 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE