

Teste a snodo SI DSIL25-PK-DURBAL - DSIL25-PK-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/dsil25-pk-durbal>

DSIL25-PK



female thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.


rod end body: surface case plated

Sliding combination: steel / bronze-PTFE composite

inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number	measurement (mm)					
	d	G	B	C1	d2	d3
right hand thread	25	M 24 x 2	31	22,00	61	33,5
DSIL 25 PK						42

type	measurement (mm)			alpha [°]	load rating C ₀ (kN)	weight (kg)
	l ₁ min	W	h			
DSI / DSIL 25 PK	42	36	94	15	85,00	0,720

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952492292
Diametro interno	25 mm
Diametro esterno	61 mm
Spessore	31 mm
Tipo	SI
Peso	720 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE