

## Teste a snodo SI SI25-PK-DURBAL - SI25-PK-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/si25-pk-durbal>

### SI25-PK



female thread; maintenance free, according to DIN ISO 12240-4, series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.


rod end body: surface case plated

Sliding combination: steel / bronze-PTFE composite

inner ring: bearing steel hardened and ground

Outer ring: rod end body pressed around, outer race lined with bronze-PTFE composite

Lubrication: maintenance free



order number	measurement (mm)							
SI 25 PK	d	G	s	C1	d1	d2	d3	d4
SI 25 PK	25	M 24 x 2	31	22,00	61	33,5	42	

type	measurement (mm)				load rating	weight
SI / SIL 25 PK	ly min	w	h	alpha [°]	C0 (kN)	(kg)
SI / SIL 25 PK	42	36	94	15	85,00	0,720

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952492315
Diametro interno	25 mm
Diametro esterno	61 mm
Spessore	31 mm
Tipo	SI
Peso	720 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE