

Teste a snodo SA DSA5-BK-DURBAL - DSA5-BK-DURBAL


<https://www.123cuscineTTi.ch/cuscineTTi-supporti/teste-snodo/sa/dsa5-bk-durbal>

DSA5-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



Rod end body:
surface zinc plated
Sliding combination:
steel / bronze-PTFE composite
Inner ring:
bearing steel hardened and ground
Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite
Lubrication:
maintenance free

order number	measurement [mm]		measurement [mm]			
	d	G	B	C ₁	d ₂	
DSA 5 BK	5	M 5	8	6,0	19	

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [g]
	l ₁ min	h			
DSA / DSAL 5 BK	20	33	12	6,00	0,014

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952492322
Diametro interno	5 mm
Diametro esterno	19 mm
Spessore	8 mm
Tipo	SA
Peso	14 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscineTTi.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE