

## Teste a snodo SA DSA6-BK-DURBAL - DSA6-BK-DURBAL


<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/dsa6-bk-durbal>

### DSA6-BK



male thread;  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



rod end body:  
surface zinc plated  
sliding combination:  
steel / bronze-PTFE composite  
inner ring:  
bearing steel hardened and ground  
Outer ring:  
rod end pressed around, outer race  
lined with bronze-PTFE composite  
Lubrication:  
maintenance free

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
DSA 6 BK		6	M 6	9	6,7	21
type	measurement [mm]		α [°]	load rating C <sub>0</sub> [kN]	weight [g]	
	l <sub>1</sub> min	h				
DSA / DSAL 6 BK	22	36	11	7,65	0,020	

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952492391
Diametro interno	6 mm
Diametro interno	0.236" inch
Diametro esterno	21 mm
Diametro esterno	0.827" inch
Spessore	9 mm
Spessore	0.354" inch
Tipo	SA
Peso	20 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE