

Teste a snodo SA SAL12-BK-DURBAL - SAL12-BK-DURBAL


<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/sal12-bk-durbal>

SAL12-BK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series K

Description: DIN ISO rod end K series. Sliding combination steel / bronze-PTFE composite.



Rod end body:

surface zinc plated

Sliding combination:
steel / bronze-PTFE composite

Inner ring:
bearing steel hardened and ground

Outer ring:
rod end body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
maintenance free

order number	measurement [mm]		measurement [mm]		
	d	G	B	C ₁	d ₂
SAL 12 BK	12	M 12	16	12,0	33

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [g]
	l ₁ min	h			
SA / SAL 12 BK	33	54	13	24,00	0,085

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952492506
Diametro interno	12 mm
Diametro esterno	33 mm
Spessore	16 mm
Tipo	SA
Peso	85 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE