

Teste a snodo SA GAL8-UK-DURBAL - DGAL8-UK-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/dgal8-uk-durbal>


GAL8-UK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

| order number | right hand thread | left hand thread | measurement (mm) | | | | |
|--------------|-------------------|------------------|------------------|-----|---|----------------|----------------|
| GAL 8 UK | | | d | g | B | C ₁ | d ₂ |
| | | | 8 | M 8 | 8 | 6,0 | 24 |

| type | l ₁ min | measurement (mm) l ₂ min | h | α [°] | load rating C ₀ [kN] | weight [kg] |
|----------------|--------------------|--|----|-------|------------------------------------|----------------|
| GAR / GAL 8 UK | 22 | 14 | 42 | 15 | 12,9 | 0,029 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|------------------|
| Marchio | DURBAL |
| N° Ean13 | 3663952492810 |
| Diametro interno | 8 mm |
| Diametro esterno | 24 mm |
| Spessore | 8 mm |
| Tipo | SA |
| Peso | 29 g |
| Il filo | Filetto sinistro |
| Lubrificazione | senza |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE