

Teste a snodo SA GAL15-UK-DURBAL - GAL15-UK-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/gal15-uk-durbal>


GAL15-UK



male thread;
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	d	g	measurement (mm)	C ₁	d ₂
right hand thread left hand thread GAL 15 UK	15	M 14	12	10,0	40

type	l, min	measurement (mm) l, min	h	a [°]	load rating C ₀ [kN]	weight [kg]
GAR / GAL 15 UK	34	20	63	8	36,0	0,140

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952492940
Diametro interno	15 mm
Diametro esterno	40 mm
Spessore	12 mm
Tipo	SA
Peso	140 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE