

Teste a snodo SA GAR17-UK-DURBAL - GAR17-UK-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/gar17-uk-durbal>


GAR17-UK



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	measurement (mm)					
right hand thread	d	G	B	C ₁	d ₂	
left hand thread						
GAR 17 UK	17	M 16	14	11,0	46	

type	l ₁ min	measurement [mm]	h	α [°]	load rating C ₀ [kN]	weight [kg]
GAR / GAL 17 UK	36	23	69	10	45,0	0,190

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952493022
Diametro interno	17 mm
Diametro interno	0.669" inch
Diametro esterno	46 mm
Diametro esterno	1.811" inch
Spessore	14 mm
Spessore	0.551" inch
Tipo	SA
Peso	190 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE