

Teste a snodo SA GAR30-UK-2RS-DURBAL - DGAR30-UK-2RS-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/dgar30-uk-2rs-durbal>


GAR30-UK-2RS



male thread:
maintenance free,
according to
DIN ISO 12240-4,
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body ground around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free

order number	measurement (mm)					
right hand thread	d	g	s	C ₁	d ₂	
GAR 30 UK (-2RS)	30	M 30 x 2	22	19,0	73	

type	measurement (mm)		h	α [°]	load rating C ₀ [kN]	weight (kg)
	l ₁ min	l ₂ min				
GAR / GAL 30 UK-2RS	65	37	110	6	110,0	0,890

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952493220
Diametro interno	30 mm
Diametro esterno	73 mm
Spessore	22 mm
Tipo	SA
Peso	897 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE