

## Teste a snodo SA GAL30-UK-DURBAL - GAL30-UK-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/gal30-uk-durbal>


### GAL30-UK



male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	d	G	B	C <sub>1</sub>	d <sub>2</sub>
right hand thread left hand thread <b>GAL 30 UK</b>	30	M 30 x 2	22	19,0	73

type	l <sub>1</sub> min	l <sub>2</sub> min	h	α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
GAR / GAL 30 UK	65	37	110	6	110,0	0,890

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952493268
Diametro interno	30 mm
Diametro esterno	73 mm
Spessore	22 mm
Tipo	SA
Peso	890 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE