

## Snodi sferici GE GAR50-UK-2RS-DURBAL - GAR50-UK-2RS-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/gar50-uk-2rs-durbal>


### GAR50-UK-2RS



male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	measurement (mm)					
right hand thread	d	g	s	C <sub>1</sub>	d <sub>2</sub>	
left hand thread						
<b>GAR 50 UK-2RS</b>	50	M 45 x 3	35	30,0	112	

type	l <sub>1</sub> min	measurement (mm)	h	a	load rating	weight
GAR / GAL 50 UK-2RS	107	60	185	6	290,0	3,400

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3616060467737
Diametro interno	50 mm
Diametro esterno	112 mm
Spessore	35 mm
Tipo	GE
Peso	3400 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1
Standard	Nessuno standard

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE