

## Teste a snodo SA GAL70-UK-2RS-DURBAL - GAL70-UK-2RS-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/gal70-uk-2rs-durbal>


### GAL70-UK-2RS



male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGAR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body ground around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free

order number	measurement (mm)		measurement (mm)			
right hand thread	left hand thread	d	g	B	C <sub>1</sub>	d <sub>2</sub>
GAL 70 UK-2RS		70	M 56 x 4	49	42,0	160

type	measurement (mm)		h	α [°]	load rating C <sub>0</sub> [kN]	weight (kg)
	l <sub>1</sub> min	l <sub>2</sub> min				
GAR / GAL 70 UK-2RS	125	87	235	6	610,0	8,200

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952493503
Diametro interno	70 mm
Diametro esterno	160 mm
Spessore	49 mm
Tipo	SA
Peso	8200 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE