

Teste a snodo SI
GIL6-UK-DURBAL - GIL6-UK-DURBAL


<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/gil6-uk-durbal>

GIL6-UK

female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq 35$ with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq 17$ additional seal on both sides upon request.



FERROBAL

Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary, maintenance free

order number	with hand rings	d	G	B	C1	d2	d4
GIL 6 UK		6	M 6	6	4,4	21	10,0 13

type	measurement [mm]			α [°]	load rating C_0 [kN]	weight [kg]
	l_3 min	h	W			
GIR / GIL 6 UK	11	30	11	13	8,2	0,021

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952493589
Diametro interno	6 mm
Diametro esterno	21 mm
Spessore	6 mm
Tipo	SI
Peso	21 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE