


Teste a snodo SI
GIR30-UK-2RS-DURBAL - GIR30-UK-2RS-DURBAL
<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/gir30-uk-2rs-durbal>

GIR30-UK-2RS

female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq 35$ with additional seal on both sides (e.g. DGIR... UK-2RS) bore diameter $d \geq 17$ additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary, maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₄	
GIR 30 UK (-2RS)		30	M 30 x 2	22	19,0	73	40,0 50	

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIL 30 UK	56	110	41	6	110,0	0,930

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952494012
Diametro interno	30 mm
Diametro esterno	73 mm
Spessore	22 mm
Tipo	SI
Peso	930 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE