

## Teste a snodo SI GIR35-UK-2RS-DURBAL - GIR35-UK-2RS-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/gir35-uk-2rs-durbal>

### GIR35-UK-2RS



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free



order number	measurement [mm]			
GIR 35 UK-2RS	d	G B C <sub>1</sub> C <sub>2</sub> d <sub>2</sub> d <sub>4</sub> h W		
	35	M 36 x 3 25 21,0 82 47,0 58		
type	measurement [mm]		load rating	weight
GIR / GIL 35 UK-2RS	t <sub>3</sub> min	h W	C <sub>0</sub> (kN)	[kg]
	60	125 50	146,0	1,300

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952494081
Diametro interno	35 mm
Diametro esterno	82 mm
Spessore	25 mm
Tipo	-
Peso	1300 g
Il filo	-
Lubrificazione	-
Imballaggio	-

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE