

## Teste a snodo SI GIR45-UK-2RS-DURBAL - GIR45-UK-2RS-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/gir45-uk-2rs-durbal>

### GIR45-UK-2RS



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free



order number	measurement [mm]			
right hand thread	left hand thread			
GIR 45 UK-2RS	45	M 42 x 3		
	32	27,0		
	102	58,0		
	70			
type	measurement [mm]		load rating	weight
	$t_2$ min	h	$C_0$ [kN]	[kg]
GIR / GIL 45 UK-2RS	65	145	240,0	2,500

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952494166
Diametro interno	45 mm
Diametro esterno	102 mm
Spessore	32 mm
Tipo	SI
Peso	2500 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE