

Teste a snodo SI GIR60-UK-2RS-DURBAL - GIR60-UK-2RS-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/gir60-uk-2rs-durbal>

GIR60-UK-2RS



female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter $d \geq$ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter $d \geq$ size 17 additional seal on both sides upon request.

Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
steel body pressed around, outer race
lined with bronze-PTFE composite

Lubrication:
no lubrication necessary,
maintenance free



order number	measurement [mm]					
right hand thread	left hand thread					
GIR 60 UK-2RS	60	M 52 x 3				
	44	38,0				
	135	70,0				
	88					
type	measurement [mm]		load rating	weight		
	t_2 min	h	C_0 [kN]	[kg]		
GIR / GIL 60 UK-2RS	70	175	75	6	450,0	5,500

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952494241
Diametro interno	60 mm
Diametro esterno	135 mm
Spessore	44 mm
Tipo	SI
Peso	5500 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE