

## Teste a snodo SI GIR70-UK-2RS-DURBAL - GIR70-UK-2RS-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/gir70-uk-2rs-durbal>

### GIR70-UK-2RS



female thread:  
maintenance free,  
according to  
DIN ISO 12240-4;  
series E

**Description:** DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter  $d \geq$  size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter  $d \geq$  size 17 additional seal on both sides upon request.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / bronze-PTFE fabric

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
steel body pressed around, outer race  
lined with bronze-PTFE composite

Lubrication:  
no lubrication necessary,  
maintenance free



order number	measurement [mm]		measurement [mm]				load rating		weight
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	kg
GIR 70 UK-2RS		70	M 56 x 4	49	42,0	160	80,0	98	
type	measurement [mm]			alpha	load rating	weight			
GIR / GIL 70 UK-2RS	t <sub>3</sub> min	h	W	°	C <sub>0</sub> [kN]	kg			
	80	200	85	6	610,0	8,600			

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952494296
Diametro interno	70 mm
Diametro esterno	160 mm
Spessore	49 mm
Tipo	SI
Peso	8600 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE