



Teste a snodo SA POSL8-DURBAL - POSL8-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/posl8-durbal>

POSL8 

Description: DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required

order number		G		measurement [mm]		
right hand thread	left hand thread	B	M	B	C ₁	d ₁
POSL 8		8	M 8	12	9,00	22

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
POS / POSL 8	25	42	14	11,6	0,030

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952494456
Diametro interno	8 mm
Diametro esterno	22 mm
Spessore	12 mm
Tipo	-
Peso	30 g
Il filo	-
Lubrificazione	-
Imballaggio	-
Standard	-

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE