

## Teste a snodo SA POS25-DURBAL - POS25-DURBAL


<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/pos25-durbal>

### POS25



Description: DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread:  
maintenance free,  
according to  
DIN ISO 12240-4,  
series K



Rod end body:

surface zinc plated

Sliding combination:

steel / heavy duty bronze

Inner ring:

bearing steel, hardened, ground and

spherical surface chromium plated

Outer ring:

heavy duty bronze with lubrication

Lubrication:

lubrication required

order number	right hand thread		left hand thread		measurement [mm]		
	d	G	B	C <sub>1</sub>	d <sub>1</sub>	h	α
POS 25	25	M 24 x 2	31	22,00	60		

type	measurement [mm]		α [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>1</sub> min	h			
POS / POSL 25	57	94	15	68,0	0,640

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952494777
Diametro interno	25 mm
Diametro esterno	60 mm
Spessore	31 mm
Tipo	SA
Peso	640 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE