



Teste a snodo SA POS28-DURBAL - POS28-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/pos28-durbal>

POS28 

Description: DIN ISO rod end K series. Sliding combination steel / heavy duty bronze.

male thread:
maintenance free,
according to
DIN ISO 12240-4,
series K



Rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required

order number	right hand thread	left hand thread	measurement [mm]				
			B	C ₁	d ₁	d ₂	
POS 28			28	M 27 x 2	35	24,00	66

type	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	h			
POS / POSL 28	62	103	15	75,5	0,960

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952494821
Diametro interno	28 mm
Diametro interno	1.102" inch
Diametro esterno	66 mm
Diametro esterno	2.598" inch
Spessore	35 mm
Spessore	1.378" inch
Tipo	SA
Peso	960 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE