

Teste a snodo SI SIZP4-S-DURBAL - SIZP4-S-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/sizp4-s-durbal>

SIZP4-S



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

female thread: lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches


rod end body: surface zinc plated

Sliding combination: steel / heavy duty bronze

inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: heavy duty bronze with lubrication

Lubrication: lubrication required, with grease nipple



order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SIZP 4 S		4,83	10 - 32	7,92	6,35	15,88	7,54	10,31

type	inches	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
		l ₁ min	W	h			
SIZP / SIZPL 4 S		14,27	7,92	26,97	10	4,6	0,015

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952495613
Diametro interno	4.83 mm
Diametro esterno	15.88 mm
Spessore	7.92 mm
Tipo	-
Peso	15 g
Il filo	-
Lubrificazione	-
Imballaggio	-

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE