

Teste a snodo SI SIZPL9-S-DURBAL - SIZPL9-S-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/si/sizpl9-s-durbal>

SIZPL9-S



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

female thread: lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches


rod end body: surface zinc plated

Sliding combination: steel / heavy duty bronze

inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: heavy duty bronze with lubrication

Lubrication: lubrication required, with grease nipple



order number		measurement [mm]	
right hand thread	left hand thread	d	G
SIZPL 9 S		9,53	3/8 - 24
			B
			C1
			d2
			d3
			d4

type	inches	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
		l ₁ min	W	h			
SIZP / SIZPL 9 S	3 / 8 "	23,80	14,27	41,28	9	10,0	0,061

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952495736
Diametro interno	9.53 mm
Diametro esterno	25.4 mm
Spessore	12.7 mm
Tipo	SI
Peso	61 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE