

Snodi sferici GE SIZPL25-S-DURBAL - SIZPL25-S-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/ge/sizpl25-s-durbal>

SIZPL25-S



Description: DIN ISO rod end K series. Dimensions in inch. Sliding combination steel / heavy duty bronze. With grease nipple.

female thread: lubrication required, similar to DIN ISO 12240-4, series K, measurement in inches


rod end body: surface zinc plated

Sliding combination: steel / heavy duty bronze

inner ring: bearing steel, hardened, ground and spherical surface chromium plated

Outer ring: heavy duty bronze with lubrication

Lubrication: lubrication required, with grease nipple



order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SIZPL 25 S		25,40	54 - 12	34,93	25,40	69,85	37,72	44,45

type	inches	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
		l ₁ min	W	h			
SIZP / SIZPL 25 S	1"	53,98	38,10	104,78	14	101,0	1,000

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3616060467843
Diametro interno	25.4 mm
Diametro interno	1" inch
Diametro esterno	69.85 mm
Diametro esterno	2 3/4" inch
Spessore	34.93 mm
Spessore	1 3/8" inch
Tipo	GE
Peso	1000 g
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE