

Teste a snodo SA DSAZPL4-S-DURBAL - DSAZPL4-S-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/dsazpl4-s-durbal>


DSAZPL4-S



male thread:
lubrication
required,
similar to
DIN ISO 12240-4:
series K,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in
inch. Sliding combination steel / heavy duty bronze.
With grease nipple.



Rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required, with grease nipple

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
DSAZPL 4 S		4,83	10 - 32	7,92	6,35	15,88

type	inches	measurement [mm]		α [°]	load rating C ₀ [kN]	weight [g]
		h ₁ min	h			
DSAZP / DSAZPL 4 S		19,05	31,75	10	3,8	0,013

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496009
Diametro interno	4.83 mm
Diametro esterno	15.88 mm
Spessore	7.92 mm
Tipo	SA
Peso	13 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE