

Teste a snodo SA SAZP9-S-DURBAL - SAZP9-S-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/sazp9-s-durbal>


SAZP9-S



male thread:
lubrication
required,
similar to
DIN ISO 12240-4:
series R,
measurement in
inches



Description: DIN ISO rod end K series. Dimensions in
inch. Sliding combination steel / heavy duty bronze.
With grease nipple.



Rod end body:
surface zinc plated

Sliding combination:
steel / heavy duty bronze

Inner ring:
bearing steel, hardened, ground and
spherical surface chromium plated

Outer ring:
heavy duty bronze with lubrication

Lubrication:
lubrication required, with grease nipple

order number		measurement [mm]	
right hand thread	left hand thread	d	G
SAZP 9 S		9,53	3/8 - 24
			B
			12,70
			C ₁
			10,31
			d ₂
			25,40

type	inches	measurement [mm]		load rating	weight
		h ₁ min	h	C ₀ [kN]	W [g]
SAZP / SAZPL 9 S	3 / 8"	31,75	49,23	9	10,0
					0,055

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496115
Diametro interno	9.53 mm
Diametro esterno	25.4 mm
Spessore	12.7 mm
Tipo	SA
Peso	55 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE