

## Teste a snodo SA SAZPL19-S-DURBAL - SAZPL19-S-DURBAL

<https://www.123cuscinetti.ch/cuscinetti-supporti/teste-snodo/sa/sazpl19-s-durbal>


### SAZPL19-S



male thread:  
lubrication  
required,  
similar to  
DIN ISO 12240-4:  
series R,  
measurement in  
inches



Description: DIN ISO rod end K series. Dimensions in  
inch. Sliding combination steel / heavy duty bronze.  
With grease nipple.



Rod end body:  
surface zinc plated

Sliding combination:  
steel / heavy duty bronze

Inner ring:  
bearing steel, hardened, ground and  
spherical surface chromium plated

Outer ring:  
heavy duty bronze with lubrication

Lubrication:  
lubrication required, with grease nipple

order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C <sub>1</sub>	d <sub>2</sub>
SAZPL 19 S		19,05	3/4 - 16	22,23	17,45	44,45

type	inches	measurement [mm]		α	load rating	weight
		h <sub>1</sub> min	h	[°]	C <sub>0</sub> [kN]	W [g]
SAZP / SAZPL 19 S	3 / 4 "	44,45	73,03	10	29,0	0,290

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952496269
Diametro interno	19.05 mm
Diametro esterno	44.45 mm
Spessore	22.23 mm
Tipo	SA
Peso	290 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE